



CCI
ControlCavi Industria



UX P15

Nominal dimensional and electrical data

1000Volt

| CONSTRUCTION (mm) | CONDUCTOR DIAMETER (APPROX (mm) | INSULATION THICKNESS (mm) | OVERALL DIAMETER (APPROX (mm) | WEIGHT (APPROX) (kg/km) | COPPER CONTENT (APPROX) (kg/km) |
|----------------------|--|---------------------------------|--|-------------------------------|--|
|----------------------|--|---------------------------------|--|-------------------------------|--|

| | | | | | |
|-------|-------|-----|------|------|------|
| 1x6 | 3,15 | 1,0 | 5,5 | 80 | 54 |
| 1x10 | 4,05 | 1,0 | 6,5 | 120 | 87 |
| 1x16 | 5,20 | 1,0 | 7,5 | 180 | 144 |
| 1x25 | 6,45 | 1,2 | 9,0 | 275 | 225 |
| 1x35 | 7,65 | 1,2 | 10,5 | 365 | 315 |
| 1x50 | 9,00 | 1,4 | 12,0 | 515 | 430 |
| 1x70 | 10,90 | 1,4 | 14,5 | 725 | 625 |
| 1x95 | 12,60 | 1,6 | 16,5 | 975 | 850 |
| 1x120 | 14,20 | 1,6 | 18,5 | 1225 | 1085 |
| 1x150 | 15,90 | 1,8 | 20,5 | 1520 | 1345 |
| 1x185 | 17,75 | 2,0 | 22,5 | 1880 | 1675 |
| 1x240 | 20,15 | 2,2 | 25,0 | 2440 | 2190 |
| 1x300 | 22,60 | 2,4 | 27,5 | 3075 | 2770 |